




Table				
TDE P/N	CUST. P/N	HUB FACE	APPROX. OVERALL LENGTH	SPRING CENTER RANGE
49543	F74G	69.00 +/-0.25	74.00	54.00 - 59.00

REVISION HISTORY				
REV	DATE	EFFCTV.	BY	DESCRIPTION
1	5/1/2008	R.C.	TJP	MADE DRAWING ONE PAGE, ADDED OAL. LENGTH TO CHART
2	8/4/2008	R.C.	TJP	ADDED ITEMS 4.1-4.3
3	7/27/2009	R.C.	TJP	10520(45022), 10560(11001), 10634(10665)
4	12/17/2009	R.C.	TJP	CORRECTED AXLE TABLE, ADDED TOLS. TO TABLE
5	8/5/2010	R.C.	TJP	REARRANGED DIMENSIONS, CLEANED UP DRAWING




NOTES:

- 1) AXLE FINISH - GALVANIZED.
- 2) 1.0° CAMBER PER SIDE WEDLED AT SPINDLES.
- 3) NO SPRING HOLES.
- 4) LIGHTLY COAT SPINDLES WITH GREASE TO PREVENT RUST.
- 5) DRILL 5/16" Dia. DRAIN HOLE IN BOTTOM OF AXLE TUBE.



Parts List			
ITEM	QTY	PART NUMBER	DESCRIPTION
1	1	49543-1	18813.288(2.0 X 2.0 X 11 GA) X 62.97" SQ.TUBING
2	2	80128	SPINDLE 1350# FOR 1-1/16" BEARINGS
3	2	12100	SUPER LUBE GREASE ZERK
4	2	10634	NUT SPINDLE 1-14 UNS 2B 12 CASTLE
5	2	10520	WASHER FLAT SPINDLE 1IN
6	2	10560	PIN COTTER 5/32X2 ZINC

CONFIDENTIALITY NOTICE: THIS DRAWING AND ALL INFORMATION CONTAINED WITHIN IT ARE THE PROPERTY OF TIE DOWN ENGINEERING, ATLANTA, GA 30336. ALL RIGHTS ARE RESERVED.

Date: 8/5/2010	Unspecified Tolerances:	 Tie Down Engineering 5901 Wheaton Drive Atlanta Georgia 0336
Design: tprelac	Fractions ± 1/32	
Drawn:	Decimal ± .06	
Approved:	Decimal ± .030	
	Angles ± 0.25°	
	Holes ± .008	2000# STRAIGHT SPRING AXLE 69.0" HUB FACE NO SPRING CENTERS Part No.: 49543

Page: 1 of 1 Rev.: 5