

Specifications	B32013	B32014	B32020MAM	B32021MAM
Typical Application	Quicksilver	OMC	MerCruiser	OMC
Engine Type	Outboard (only)	Outboard (only)	Inboard/Outboard	Inboard/Outboard
UL Recognized Component	No	No	Yes	Yes
Maximum Flow Rate	60 GPH (227 LPH)	60 GPH (227 LPH)	60 GPH (227 LPH)	60 GPH (227 LPH)
Replacement Element	S3213	S3214	S3220UL	S3221TUL
Center Threads	11/16"-16	1"-12	11/16"-16	1"-12
Height	7.2 in. (18.2 cm)	7.2 in. (18.2 cm)	6.5 in. (16.5 cm)	6.5 in. (16.5 cm)
Diameter	3.8 in. (9.7 cm)	3.8 in. (9.7 cm)	3.8 in. (9.7 cm)	3.8 in. (9.7 cm)
Weight (dry)	1.2 lbs (0.5 kg)	1.2 lbs (0.5 kg)	1.6 lbs (0.7 kg)	1.6 lbs (0.7 kg)
Clean Pressure Drop	0.6 PSI (4.32 kPa)	0.6 PSI (4.32 kPa)	0.6 PSI (4.32 kPa)	0.6 PSI (4.32 kPa)
Under Bowl Clearance	1.0 in. (2.5 cm)	1.0 in. (2.5 cm)	1.0 in. (2.5 cm)	1.0 in. (2.5 cm)
Bowl Type	Clear	Clear	Metal	Metal
Water Removal Efficiency	99%	99%	99%	99%
Case Quantity	12	12	12	12
Ambient Fuel Temperature	-40° to +250°F (-40° to +121°C)			