



## PRODUCT DATA SHEET

Marine Boat Trailer and 4x4 Wheel Bearing Grease, 14 Wt Oz  
Part Number: SL3120

### Product Description

A blue tacky, aluminum complex grease using a highly refined base oil. It has been formulated with a polymer to provide adhesive, non-blend and water wash-out characteristics. Will resist water under the most severe water conditions.

### Applications

Anti-friction bearings, blocks, boat trailer bearings, deck equipment, marine equipment, shaft log seals, sleeve bearings, slides, steering cables, steering dockside machinery, steering quadrants, turnbuckles, wheel bearings, winches

### Unit Package Description

14 Ounce Cartridge

### Brand

Sta-Lube

### Generic Description 1

Marine Grease for Boat Trailer

### Net Fill

14 Wt Oz

### UPC Code

072213312003

### Unit Dimensions

9.31H x 2.13W x 2.13D in

### Units Per Case

10

### Case Dimensions

9.5H x 4.5W x 11.38D in

### Cases Per Pallet

150

### Case Weight

11 lbs

### I 2 of 5 Code

30072213312004

### Appearance

Blue Semi-Solid to Solid Grease

### Base Type

Aluminum Complex

### Flash point (F)

>450°F

### Flash point (C)

>232°C

### Flammability Class - CPSC

None

### Spec Gravity Concentrate

0.9 at 60°F

### NLGI Grade

2

### Plastic Safe

Not Determined

### Evaporation Rate

<0.01 (Butyl Acetate=1)



Last revised: 5/4/2016  
Page 1 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
[www.crcindustries.com](http://www.crcindustries.com)

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



## PRODUCT DATA SHEET



Working Temp (F)	0 to 325°F
Working Temp (C)	-17.8 to 162°C
Drop Point	500°F
Leakage	5
Oxidation Stability	5
Pour Point (F)	0°F
Pour Point (C)	-17.78°C
ISO Viscosity Grade	180
Water Washout	5
Worked Penetration	265 to 295
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Federal)	0
VOC g/L (Federal)	0
VOC Lbs./Gal. (Federal)	0
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.

Last revised: 5/4/2016  
Page 2 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
[www.crcindustries.com](http://www.crcindustries.com)

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.