



**NOTE:**

MATERIAL: PIN: 1008 CARBON STEEL  
 SPRING MEDIUM: SAINLESS STEEL  
 BALL: 302 STAINLESS STEEL  
 RING: HARD DRAWN WIRE  
 LANYARD: SUPER TOUGH NYLON (35 L.B. MIN. BREAKING STRENGTH)

HEAT TREAT: NONE

FINISH: PIN & RING: ZINC W/ CLEAR

**A** BALL PRESSURE AT FLUSH IS:  
 8-14 LBS USING STAINLESS STEEL SPRING

BALL TO RING HOLE ALIGNMENT IS RANDOM

ALL DIMENSIONS ARE IN INCHES  
 UNLESS OTHERWISE STATED  
 TOLERANCES EXCEPT AS NOTED

**DECIMALS:**

.X ±0.100  
 .XX ±0.060  
 .XXX ±0.030  
 .XXXX ±0.010

**ANGLES:**

±1°  
 ALL FORMED ANGLES  
 EQUAL 90° UNLESS  
 NOTED OTHERWISE

( ) INDICATES REFERENCE

THE INFORMATION IN THIS DRAWING IS THE SOLE  
 PROPERTY OF KARAVAN TRAILERS, INC. ANY  
 REPRODUCTION IN PART OR WHOLE WITHOUT  
 THE WRITTEN PERMISSION OF KARAVAN TRAILERS,  
 INC. IS PROHIBITED.

**APPROVED BY:**

---

**DRAWN BY:**

TODD VAN HERWAARDEN

**DATE:**

09-09-16

**SHEET:**

1 OF 1

**SCALE:**

N/A

**KARAVAN**

**TITLE:**

QUICK RELEASE PIN

**MAT'L:**

PURCHASED

**FINISH:**

N/A

**DWG. #:**

**207-00045-C**

DWG. REV.	ECR/NDR NUMBER	REVISED BY	DATE	DESCRIPTION
C	15961	MCS	03-21-17	UPDATED PRINT TO PART
B	15961	TVH	09-22-16	3.625 WAS 4.00